

# Package: electivity (via r-universe)

August 26, 2024

**Type** Package

**Title** Algorithms for Electivity Indices

**Version** 1.0.2

**Date** 2019-08-13

**Description** Provides all electivity algorithms (including Vanderploeg and Scavia electivity) that were examined in Lechowicz (1982) <[doi:10.1007/BF00349007](https://doi.org/10.1007/BF00349007)>, plus the example data that were provided for moth resource utilisation.

**URL** <https://github.com/DesiQuintans/electivity>

**BugReports** <https://github.com/DesiQuintans/electivity/issues>

**Encoding** UTF-8

**LazyData** true

**Depends** R (>= 3.4.0)

**Suggests** utils (>= 3.4.2), usethis (>= 1.0.0)

**RoxygenNote** 6.1.1

**License** MIT + file LICENSE

**Repository** <https://desiquintans.r-universe.dev>

**RemoteUrl** <https://github.com/desi quintans/electivity>

**RemoteRef** HEAD

**RemoteSha** deb4f4abea7437ab2b1353cf1ab994c2424cc30b

## Contents

chesson_alpha . . . . .	2
electivity . . . . .	3
ivlev_electivity . . . . .	3
ivlev_forage . . . . .	4
jacob_electivity . . . . .	5
jacob_forage . . . . .	5
moth_distrib . . . . .	6

moth_elect . . . . .	7
strauss_linear . . . . .	8
vs_electivity . . . . .	8

<b>Index</b>	<b>10</b>
--------------	-----------

---

chesson_alpha	<i>Chesson's alpha, or Vanderploeg and Scavia's selectivity coefficient (W)</i>
---------------	---

---

### Description

These two functions calculate the same value; alpha and W are identical.

### Usage

```
chesson_alpha(r, p, na.rm = TRUE)
```

```
vs_select_coef(r, p, na.rm = TRUE)
```

### Arguments

r	(Numeric) Resource utilisation.
p	(Numeric) Resource availability.
na.rm	(Logical) If 'TRUE', 'NA's will be ignored when calculating the selectivity coefficient (W).

### Value

A numeric vector.

### Examples

```
data(moth_distrib)

chesson_alpha(moth_distrib$r, moth_distrib$p)
vs_select_coef(moth_distrib$r, moth_distrib$p)
```

---

electivity	<i>Algorithms for electivity indices and measures of resource use versus availability.</i>
------------	--

---

### Description

This package is essentially Lechowicz (1982) turned into an R package. It includes all algorithms that were described therein plus the example data that was provided for moth resource utilisation.

### Details

Lechowicz, M.J., 1982. The sampling characteristics of electivity indices. *Oecologia* 52, 22–30. <https://doi.org/10.1007/BF00349007>

Users are encouraged to read the original paper before deciding which algorithm is most useful for them. Lechowicz recommended Vanderploeg and Scavia's E\* index (implemented in this package as `vs_electivity()`) as "the single best, but not perfect, electivity index" because "E\* embodies a measure of the feeder's perception of a food's value as a function of both its abundance and the abundance of other food types present." In practice, he found that all indices returned nearly identical rank orders of preferred hosts except for Strauss' linear index (L).

### Author

Desi Quintans (@eco\_desi)

### URL

<https://github.com/DesiQuintans/electivity/>

---

<code>ivlev_electivity</code>	<i>Ivlev's electivity, E</i>
-------------------------------	------------------------------

---

### Description

Bounded between -1.0 (avoidance), 0 (random feeding), and +1.0 (preference).

### Usage

```
ivlev_electivity(r, p)
```

### Arguments

r	(Numeric) Resource utilisation.
p	(Numeric) Resource availability.

**Value**

A numeric vector.

**Source**

Lechowicz, M.J., 1982. The sampling characteristics of electivity indices. *Oecologia* 52, 22–30.  
<https://doi.org/10.1007/BF00349007>

**Examples**

```
data(moth_distrib)
ivlev_electivity(moth_distrib$r, moth_distrib$p)
```

---

ivlev_forage	<i>Ivlev's forage ratio, E'</i>
--------------	---------------------------------

---

**Description**

Bounded between +0.1 (avoidance), +1.0 (random feeding), and infinity (preference).

**Usage**

```
ivlev_forage(r, p, log10 = FALSE)
```

**Arguments**

**r** (Numeric) Resource utilisation.  
**p** (Numeric) Resource availability.  
**log10** (Logical) If TRUE, transform the value with `log10()`.

**Value**

A numeric vector.

**Examples**

```
data(moth_distrib)
ivlev_forage(moth_distrib$r, moth_distrib$p, log10 = FALSE)
ivlev_forage(moth_distrib$r, moth_distrib$p, log10 = TRUE)
```

---

jacob_electivity	<i>Jacob's modified electivity, D</i>
------------------	---------------------------------------

---

**Description**

Bounded between +0.1 (avoidance), +1.0 (random feeding), and infinity (preference).

**Usage**

```
jacob_electivity(r, p)
```

**Arguments**

r	(Numeric) Resource utilisation.
p	(Numeric) Resource availability.

**Value**

A numeric vector.

**Examples**

```
data(moth_distrib)
jacob_electivity(moth_distrib$r, moth_distrib$p)
```

---

jacob_forage	<i>Jacob's modified forage ratio, Q</i>
--------------	---

---

**Description**

When logged (which is Jacob's recommendation), bounded between negative and positive infinity.

**Usage**

```
jacob_forage(r, p, log10 = FALSE)
```

**Arguments**

r	(Numeric) Resource utilisation.
p	(Numeric) Resource availability.
log10	(Logical) If TRUE, return the value as Log10.

**Value**

A numeric vector.

**Examples**

```
data(moth_distrib)
jacob_forage(moth_distrib$r, moth_distrib$p, log10 = TRUE)
jacob_forage(moth_distrib$r, moth_distrib$p, log10 = FALSE)
```

---

moth_distrib	<i>Distribution of gypsy moth larvae, Lymantria dispar, feeding in a deciduous forest in southwestern Quebec, Canada.</i>
--------------	---

---

**Description**

This is Table 2 in the cited source paper.

**Usage**

```
moth_distrib
```

**Format**

A dataframe with 19 rows and 6 variables:

**binomen** Species of tree.

**n\_indiv** Number of randomly sampled trees.

**dbh\_cm\_sum** Summed diameters at breast height, in centimeters.

**larva\_mean\_sum** Summed numbers of larvae (the means of two counts taken on June 26-27, 1979 and July 3-4, 1979).

**r** Relative proportion of larvae feeding on trees (Lechowicz 1982, Equation 2)

**p** Estimate of foliage biomass (Lechowicz 1982, Equation 1).

**Source**

Lechowicz, M.J., 1982. The sampling characteristics of electivity indices. *Oecologia* 52, 22–30. <https://doi.org/10.1007/BF00349007>

**Examples**

```
data(moth_distrib)
```

---

moth_elect	<i>Electivities of gypsy moth larvae</i>
------------	--

---

### Description

This is Table 3 in the cited source paper.

### Usage

```
moth_elect
```

### Format

A dataframe with 19 rows and 8 variables:

**binomen** Species of tree.

**E** Ivlev's electivity index.

**E\_prime\_i** Ivlev's forage ratio.

**D\_i** Jacob's modified electivity.

**log\_Q\_i** Jacob's modified forage ratio, log10.

**L\_i** Strauss' linear index.

**W\_i** Chesson's alpha, or Vanderploeg and Scavia's selectivity coefficient.

**E\_star\_i** Vanderploeg and Scavia's relativised electivity.

### Source

Lechowicz, M.J., 1982. The sampling characteristics of electivity indices. *Oecologia* 52, 22–30.  
<https://doi.org/10.1007/BF00349007>

### Examples

```
data(moth_elect)
```

---

strauss_linear	<i>Strauss' linear index, L</i>
----------------	---------------------------------

---

**Description**

Bounded between -1.0 (avoidance), 0 (random feeding), and +1.0 (preference).

**Usage**

```
strauss_linear(r, p)
```

**Arguments**

r	(Numeric) Resource utilisation.
p	(Numeric) Resource availability.

**Value**

A numeric vector.

**Examples**

```
data(moth_distrib)
strauss_linear(moth_distrib$r, moth_distrib$p)
```

---

vs_electivity	<i>Vanderploeg and Scavia's relativised electivity, E*</i>
---------------	--

---

**Description**

Bounded between -1.0 (avoidance), 0 (random feeding), and +1.0 (preference).

**Usage**

```
vs_electivity(r, p, na.rm = TRUE)
```

**Arguments**

r	(Numeric) Resource utilisation.
p	(Numeric) Resource availability.
na.rm	(Logical) If TRUE, NAs will be ignored when calculating the selectivity coefficient (W).

**Value**

A numeric vector.



*vs\_electivity*

9

### **Examples**

```
data(moth_distrib)
vs_electivity(moth_distrib$r, moth_distrib$p)
```

# Index

## \* data

moth\_distrib, 6  
moth\_elect, 7

chesson\_alpha, 2

electivity, 3  
electivity-package (electivity), 3

ivlev\_electivity, 3  
ivlev\_forage, 4

jacob\_electivity, 5  
jacob\_forage, 5

moth\_distrib, 6  
moth\_elect, 7

strauss\_linear, 8

vs\_electivity, 8  
vs\_select\_coef (chesson\_alpha), 2